

Product Search Data Sheet

Note: This datasheet may be out of date.

Please download the latest datasheet of NTSD1WB203FPB40 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NTSD1WB203FPB40

NTSD1WB203FPB40










Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Industrial Equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



Appearance & Shape





1XM202/NTSD1WB203/NTSD1WC303 Types		
Туре	L (mm)	
NTSD1_FPB30	30	
NTSD1_FPB40	40	
NTSD1 FPB50	50	



Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	Bulk(Bag)	200



Features

- 1. Electric insulation on lead wire
- 2. Excellent bending resistance due to suitable hardness of surface coating
- 3. Easy handling due to most suitable hardness of surface of coating
- 4. +/-1% of resistance and B-Constant tolerance is realized due to uniform thickness by the precise sheet forming method.

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





NTSD1WB203FPB40

Note: This datasheet may be out of date.

http://www.murata.com/en-us/products/productdetail?partno=NTSD1WB203FPB40

Please download the latest datasheet of NTSD1WB203FPB40 from the official website of Murata Manufacturing Co., Ltd.



Specifications

Resistance (25°C)	20kΩ
Resistance Value Tolerance (at 25°C)	±1%
B-Constant (25/50°C)	4050K
B-Constant (25/50°C) Tolerance	±1%
B-Constant(25/80°C) (Reference Value)	4078K
B-Constant(25/85°C) (Reference Value)	4080K
B-Constant(25/100°C) (Reference Value)	4096K
Maximum Operating Current (25°C)	0.1mA
Rated Electric Power (25°C)	21.0mW
Typical Dissipation Constant (25°C)	2.1mW/°C
Operating Temperature Range	-40°C to 125°C
Thermal Time Constant	7s
Lead Shape	Insulation type
Shape	Lead
Mass	0.13g
MSL	N

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






Note: This datasheet may be out of date. Please download the latest datasheet of NTSD1WB203FPB40 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NTSD1WB203FPB40

NTSD1WB203FPB40



Product Data



Temperature Tolenrance-Temperature Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

