

### Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of PVA2A222A01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PVA2A222A01B00

## PVA2A222A01B00










### Appearance & Shape





Tolerance: ±0.2 in mm



### **Features**

- 1. Ultra-small and thin external dimensions of 2.2(W)x2.75(L)x0.90 max.(T)mm.
- 2. For the terminal attachment method of construction that uses neither solder nor adhesives, good solderability and terminal attachment intensity are realized.
- 3. Because of multi-contact wiper structure, PVA2 has a stable characteristics (low noise).
- 4. PVA2 series does not use a solder, flux or cleaning solvent, so they are environmentally friendly
- 5. Heat resistance performance enables high temperature peak reflow soldering.



## Packaging Information

Packaging	Specifications	Standard Packing Quantity
B00	Bulk(Bag)	1000

1 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Note: This datasheet may be out of date. Please download the latest datasheet of PVA2A222A01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PVA2A222A01B00

# PVA2A222A01B00



# **Specifications**

Power Rating	0.1W	
Shape	SMD	
Maximum Working Voltage	50Vdc	
Adjustment Direction	Тор	
Size	2mm	
Auto Adjustment	Yes	
Number of Turns (Effective Rotation Angle)	1(260°±10°)	
Mechanical Rotation Angle	Endless	
Total Resistance Value	2.2kΩ	
Total Resistance Value Tolerance	±25%	
Temperature Coefficient of Resistance	±250ppm/°C	
Resistance Taper	B (Linear)	
Contact Resistance Variation	3% max. of nominal total resistance value	
Residual Resistance	4% max. of nominal total resistance value	
Torque	0.5 to 9.8mN ⋅ m	
Measure Condition of RatedPower	70°C	
Operating Temperature Range	-55°C to 125°C	
Mass	0.01g	

2 of 3

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.






# PVA2A222A01B00

Note: This datasheet may be out of date.

Please download the latest datasheet of PVA2A222A01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=PVA2A222A01B00





Constructions

3 of 3

### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no space for \ detailed \ specifications.}$ 

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

