

## IRH-12/21-W80NB-C

Note: This datasheet may be out of date.

Please download the latest datasheet of IRH-12/21-W80NB-C from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=IRH-12%2f21-W80NB-C









## **Applications**

Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
	Consumer equipment,Industrial
	Equipment
	Please refer to Our Website and
	specifications, etc. for information about
Specific	the performance, functions, quality,
Applications	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



### **Features**

250W, 12Vo/21A, 16V-160Vin, Isolated DC-DC Converter, Negative Logic, Meets requirements for EN50155



## Appearance & Shape



1 of 2

#### Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# IRH-12/21-W80NB-C

Note: This datasheet may be out of date.

Please download the latest datasheet of IRH-12/21-W80NB-C from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=IRH-12%2f21-W80NB-C



## **Specifications**

Output power (W)Max	250W
Vin(V)	16V to 160V
Vin(V)typ	72V
Vout(V)	12V
Vout(V)typ	12V
LineRegulation (%)	-0.2% to 0.2%
LoadRegulation (%)	-0.2% to 0.2%
Isolation Voltage (V)	4242V
Efficiency (%)	91%
Size(mm)W	60.7mm
Size(mm)L	63.2mm
Size(mm)T	14.0mm
Operatingtemperature(degC)	-40°C to 85°C
Outputs (#)	1
lout(A)Max	21A
Form	1/2 Brick
Package	DIP
Productseries	IRH-W80
Product Series Features	250W 10:1 Ultra Wide Input Encapsulated Half-Brick Isolated DC-DC Converter for Railway
Regulation	Regulated
Safety Approval	UL 60950-1, IEC/EN60950-1, 2nd Edition
Brand	Murata Power Solutions

2 of 2

#### Attentior

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

