

### Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of UWE-12/10-Q48NB-C from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=UWE-12%2f10-Q48NB-C

# UWE-12/10-Q48NB-C









## **Applications**

Please be sure to read and comply with
these "Precautions for use."
Consumer equipment,Industrial
Equipment
Please refer to Our Website and
specifications, etc. for information about
the performance, functions, quality,
management, and safety required for
the above applications, and use
Products after confirming the
performance and reliability of the actual
Product.



## **Features**

12V, 10A, Single Output Isolated 1/8 Brick DC-DC Converter, 18-75V Input Range, Negative polarity, Baseplate



# Appearance & Shape



1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





## Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of UWE-12/10-Q48NB-C from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=UWE-12%2f10-Q48NB-C

# UWE-12/10-Q48NB-C



# **Specifications**

Output power (W)Max	120W
Vin(V)	18V to 75V
Vin(V)typ	48V
Vout(V)	12V
Vout(V)typ	12V
LineRegulation (%)	0.15%
LoadRegulation (%)	0.075%
Isolation Voltage (V)	2250V
Efficiency (%)	91.5%
Size(mm)W	58.42mm
Size(mm)L	22.86mm
Size(mm)T	12.8mm
Operatingtemperature(degC)	-40°C to 85°C
Outputs (#)	1
lout(A)Max	10A
Form	1/8 Brick
Package	DIP
Productseries	UWE
Product Series Features	Quarter-brick DOSA- Compatible, Isolated DC-DC Converters
Safety Approval	These devices are designed to meet UL/CSA60950 and IEC/EN60950 safety standards, including BASIC insulation requirements. Q48 models are CE marked (meet the requirements of LVD).

Brand Murata Power Solutions	В
------------------------------	---

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

