Note: This datasheet may be out of date. Please download the latest datasheet of MYSGK02506BRSR from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=MYSGK02506BRSR

MYSGK02506BRSR

9.6V to 42V input voltage, 6A, Buck Converter with 85degC Ta









Applications

| 11 | Discount of the country of the count | |
|--------------|--|--|
| Unsuitable | Please be sure to read and comply with | |
| Applications | these "Precautions for use." | |
| | Consumer equipment,Industrial | |
| | Equipment | |
| | Please refer to Our Website and | |
| | specifications, etc. for information about | |
| Specific | the performance, functions, quality, | |
| Applications | management, and safety required for | |
| | the above applications, and use | |
| | Products after confirming the | |
| | performance and reliability of the actual | |
| | Product. | |
| Recommended | Industrial Equipment | |
| Applications | Industrial Equipment | |




Features

Input voltage ranges from 9.6 to 42V Absolute maximum input voltage: 50V Settable output voltage from 5 to 25V Up to 6 A of output current Small package, 14.7 x 16.3 x 7.5mm Short Circuit protection, Non-latching Enable control Settable UVLO



Appearance & Shape





1 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of MYSGK02506BRSR from the official website of Murata $\,$ Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=MYSGK02506BRSR

MYSGK02506BRSR



Specifications

| lout(A)Max | 6A |
|----------------------------|---|
| Vin(V) | 9.6V to 42V |
| Vin(V)typ | 24V |
| Vout(V) | 5V to 25V |
| Vout(V)typ | 12V |
| LineRegulation (%) | -2% to 2% |
| LoadRegulation (%) | -2% to 2% |
| Outputs (#) | 1 |
| Efficiency (%) | 98% |
| Switching frequency (kHz) | 380kHz |
| Size(mm)W | 14.7mm |
| Size(mm)L | 16.3mm |
| Size(mm)T | 7.5mm |
| Operatingtemperature(degC) | -40°C to 85°C |
| Circuit topology | Buck(Step-down) |
| Package | SMD |
| Туре | Modules (integrated components) |
| Productseries | MYSGK |
| Product Series Features | MYSGK series which is POL (Point of Load) is single output MonoBK. |
| Brand | Murata |

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

