

GCJ31MR71E225KA12#



< List of part numbers with package codes > GCJ31MR71E225KA12L GCJ31MR71E225KA12K

Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Automotive powertrain/safety equipment,	
	Automotive infotainment/comfort	
	equipment,Medical equipment [GHTF	
	A/B/C] except for implant equipment	
	Please refer to Our Website and	
Specific	specifications, etc. for information about	
Applications	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	

Appearance & Shape





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of GCJ31MR71E225KA12# from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=GCJ31MR71E225KA12%23

"#"at the end indicates the package specification code.

Resin external electrode products

Notices



References

Packaging	Specifications	Standard Packing
laokaging	opeonications	Quantity
L	180Embossed Tape	3000
К	330Embossed Tape	10000

Mass (typ.)	
1 piece	34.0mg

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





GCJ31MR71E225KA12#

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of GCJ31MR71E225KA12# from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=GCJ31MR71E225KA12%23

"#"at the end indicates the package specification code.



Specifications

Length	3.2±0.4mm
Width	1.6±0.3mm
Thickness	1.15±0.2mm
Capacitance	2.2µF ±10%
Distance between external terminals g	1.5mm min.
External terminal size e	0.3 to 1.0mm
Operating Temperature Range	-55°C to 125°C
Rated Voltage	25Vdc
Size code in inch(mm)	1206 (3216M)
Capacitance change rate	±15.0%
Temperature characteristics (complied standard)	X7R(EIA)
Temperature range of temperature characteristics	-55℃ to 125℃

2 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

