Note: This datasheet may be out of date.

Please download the latest datasheet of NCU18XH103F6SRB from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCU18XH103F6SRB

NCU18XH103F6SRB














Appearance & Shape







Packaging Information

Packaging		Standard Packing Quantity
RB	180mm Paper Tape	4000



Features

- 1. Excellent solderability and high stability in environment
- 2. Excellent long time aging stability
- 3. High accuracy in resistance and B-constant
- 4. Flow / Reflow soldering possible
- 5. Lead is not contained in the product.
- 6. NCU series are recognized by UL/cUL (UL1434, File No.E137188).



Applications

Limited Usage	Automotive Grade
	1. Various engine control units 2. ABS
	control unit 3. High power devices
Other Usage	(IGBT) 4. Temperature compensation
	for various circuits required high
	temperature.

1 of 3

Attention

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: This datasheet may be out of date.

Please download the latest datasheet of NCU18XH103F6SRB from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCU18XH103F6SRB

NCU18XH103F6SRB



Specifications

Resistance (25°C)	10kΩ	
Resistance Value Tolerance	+1%	
(at 25°C)	1170	
B-Constant (25/50°C)	3380K	
B-Constant (25/50°C)	±1%	
Tolerance		
B-Constant(25/80°C)	3428K	
(Reference Value)		
B-Constant(25/85°C)	3434K	
(Reference Value)	0-10-11	
B-Constant(25/100°C)	3455K	
(Reference Value)		
Max. Voltage	5V	
Maximum Operating Current	0.1mA	
(25°C)		
Typical Dissipation Constant	1mW/°C	
(25°C)		
Operating Temperature	-40°C to 150°C	
Range	+0 C 10 100 C	
Size Code (in mm)	1.6x0.8mm	
Size Code (in inch)	0.6x0.3inch	
Shape	SMD	
Mass	0.0047g	

2 of 3

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Note: This datasheet may be out of date.


Please download the latest datasheet of NCU18XH103F6SRB from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=NCU18XH103F6SRB

NCU18XH103F6SRB







Resistance-Temperature Characteristics

Maximum Operating Voltage Reduction Characteristics

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

