



Note: This datasheet may be out of date.

Please download the latest datasheet of CSTCR6M60G55B-R0 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCR6M60G55B-F

CSTCR6M60G55B-R0












Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Automotive powertrain/safety equipment Please refer to Our Website and specifications, etc. for information about the performance, functions, quality, management, and safety required for the above applications, and use Products after confirming the performance and reliability of the actual	
	Product.	



Appearance & Shape







Packaging Information

	Packaging	Specifications	Standard Packing Quantity
	R0	180mm Embossed Tape	3000



Features

MURATA's frequency adjustment and package technology expertise has enabled the development of the chip CERALOCK. This diverse series owes its development to MURATA's original mass production techniques and high reliability, and has achieved importance in the worldwide automotive market.

Features

- 1. The series has high reliability and is available for a wide temperature range.
- 2. Oscillation circuits do not require external load capacitors.
- 3. The series is available in a wide frequency range.
- 4. The resonators are extremely small and have a low profile.
- 5. No adjustment is necessary for oscillation circuits.

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: This datasheet may be out of date. $Please\ download\ the\ latest\ data sheet\ of\ CSTCR6M60G55B-R0\ from\ the\ official\ website\ of\ Murata$ Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=CSTCR6M60G55B-R0

CSTCR6M60G55B-R0



Specifications

Product Type	Ceramic Resonator	
Floudict Type	(CERALOCK)	
Series	CSTCR_G_B	
Frequency	6.600MHz	
Frequency Tolerance	+/-0.50% max.	
Operating Temperature	-40°C~125°C	
Range		
Frequency Shift by	+/-0.15% max.	
Temperature	, 0.1076	
Frequency Aging	+/-0.05% max.	
Resonant Impedance (R1)	50ohm max.	
Built-in Load Capacitance	00.5	
(CL1/CL2)	39pF	
Shape	SMD	
Wash	available	
L x W (size)	4.5x2.0mm	
Mass	29mg	

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

