

Product Search Data Sheet

PVA2A101A01B00


Note: This datasheet may be out of date. Please download the latest datasheet of PVA2A101A01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PVA2A101A01B00



Appearance & Shape







- 1. Ultra-small and thin external dimensions of 2.2(W)x2.75(L)x0.90 max.(T)mm.
- 2. For the terminal attachment method of construction that uses neither solder nor adhesives, good solderability and terminal attachment intensity are realized.
- 3. Because of multi-contact wiper structure, PVA2 has a stable characteristics (low noise).
- 4. PVA2 series does not use a solder, flux or cleaning solvent, so they are environmentally friendly products.
- 5. Heat resistance performance enables high temperature peak reflow soldering.

Packaging Information

| Packaging | Specifications | Standard Packing Quantity |
|-----------|----------------|---------------------------------|
| B00 | Bulk(Bag) | 1000 |

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





PVA2A101A01B00

Note: This datasheet may be out of date. Please download the latest datasheet of PVA2A101A01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PVA2A101A01B00

Specifications

| Power Rating | 0.1W | |
|---|---|--|
| Shape | SMD | |
| Maximum Working Voltage | 50Vdc | |
| Adjustment Direction | Тор | |
| Size | 2mm | |
| Auto Adjustment | Yes | |
| Number of Turns (Effective Rotation Angle) | 1(260°±10°) | |
| Mechanical Rotation Angle | Endless | |
| Total Resistance Value | 100Ω | |
| Total Resistance Value Tolerance | ±25% | |
| Temperature Coefficient of Resistance | ±250ppm/°C | |
| Resistance Taper | B (Linear) | |
| Contact Resistance Variation | 3% max. of nominal total resistance value | |
| Residual Resistance | 10ohm max. | |
| Torque | 0.5 to 9.8mN ⋅ m | |
| Measure Condition of RatedPower | 70°C | |
| Operating Temperature Range | -55°C to 125°C | |
| Mass | 0.01g | |

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




Product Search Data Sheet




PVA2A101A01B00

Note: This datasheet may be out of date. Please download the latest datasheet of PVA2A101A01B00 from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=PVA2A101A01B00





Constructions

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

