

Product Search Data Sheet

information provided may not be the most current.

Please download the latest datasheet of DE1B3RA151KA4BQ01F from the official website of Murata

Note: If you have not downloaded this document from our official website, please note that the

http://www.murata.com/en/products/productdetail?partno=DE1B3RA151KA4BQ01

DE1B3RA151KA4BQ01F














Applications


Unsuitable	Please be sure to read and comply with
Applications	these "Precautions for use."
Specific Applications	Consumer equipment,Industrial
	Equipment,Mobile Electronics,Medical
	equipment [GHTF A/B/C] except for
	implant equipment,Automotive
	infotainment/comfort equipment
	Please refer to Our Website and
	specifications, etc. for information about
	the performance, functions, quality,
	management, and safety required for
	the above applications, and use
	Products after confirming the
	performance and reliability of the actual
	Product.



Appearance & Shape









Notices

X1/Y1 Class Certified Products、 Halogen-free Products、 Rated Voltage X1:500Vac(r.m. s.)/1500Vdc Y1:500Vac(r.m.s.)/1500Vdc



References

		Standard
Packaging	Specifications	Packing
		Quantity
В	Bulk(Bag)	250

Mass (typ.)	
1 piece	0.4g

1 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of DE1B3RA151KA4BQ01F from the official website of Murata

DE1B3RA151KA4BQ01F



Specifications

L size or Outer diameter D 8.0mm max. T size 5.0mm max. Lead spacing F 10.0±1.0mm Lead diameter d 0.6±0.05mm Paint dripping e Up to the end of crimp Capacitance 150pF ±10% Rated voltage 500Vac(r.m.s.) Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature Range -40°C to 125°C			
Lead spacing F 10.0±1.0mm 10.6±0.05mm Paint dripping e Up to the end of crimp Capacitance 150pF ±10% Rated voltage 500Vac(r.m.s.) Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	L size or Outer diameter D	8.0mm max.	
Lead spacing F 10.0±1.0mm 10.6±0.05mm Paint dripping e Up to the end of crimp Capacitance 150pF ±10% Rated voltage 500Vac(r.m.s.) Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	T size	5 0mm max	
Lead diameter d O.6±0.05mm Paint dripping e Up to the end of crimp Capacitance 150pF ±10% Rated voltage 500Vac(r.m.s.) Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	1 0/20	o.omm max.	
Paint dripping e Up to the end of crimp Capacitance 150pF ±10% Rated voltage 500Vac(r.m.s.) Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	Lead spacing F	10.0±1.0mm	
Capacitance 150pF ±10% Rated voltage 500Vac(r.m.s.) Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	Lead diameter d	0.6±0.05mm	
Capacitance 150pF ±10% Rated voltage 500Vac(r.m.s.) Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	B : () :		
Rated voltage 500Vac(r.m.s.) Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	Paint dripping e	Up to the end of crimp	
Rated voltage 500Vac(r.m.s.) Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	Capacitance	150pF ±10%	
Temperature characteristics B(JIS) Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	Саразнанов	10061 21070	
Capacitance change rate ±10% Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	Rated voltage	500Vac(r.m.s.)	
Temperature range of temperature characteristics Operating Temperature -40°C to 125°C	Temperature characteristics	B(JIS)	
Temperature range of temperature characteristics Operating Temperature -40°C to 125°C			
temperature characteristics -25 C to 85 C Operating Temperature -40°C to 125°C	Capacitance change rate	±10%	
temperature characteristics Operating Temperature -40°C to 125°C	Temperature range of	-25°C to 85°C	
I-40°C to 125°C	temperature characteristics		
	Operating Temperature	40°C to 125°C	
	Range	-40 C to 125 C	

2 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Please download the latest datasheet of DE1B3RA151KA4BQ01F from the official website of Murata


http://www.murata.com/en/products/productdetail?partno=DE1B3RA151KA4BQ01l


DE1B3RA151KA4BQ01F





Characteristic Data

The charts below may show another part number which shares its characteristics.









3 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering




Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of DE1B3RA151KA4BQ01F from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=DE1B3RA151KA4BQ01

DE1B3RA151KA4BQ01F



DE1B3RA151KA4BQO1F C-Temp. capchange, DCOV,



DE1B3RA151KA4BQ01F S21 DCOV,20degC

4 of 4

Attention

1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

