

Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of DE6E3KJ222MN3A from the official website of Murata

DE6E3KJ222MN3A


















Applications


Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Automotive powertrain/safety equipment,	
	Automotive infotainment/comfort	
	equipment,Medical equipment [GHTF	
	A/B/C] except for implant equipment	
	Please refer to Our Website and	
Specific	specifications, etc. for information about	
Applications	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



Appearance & Shape









Notices

X1/Y2 Class Certified Products、 Halogen-free Products、 Rated Voltage X1:440Vac(r.m. s.)/Y2:300Vac(r.m.s.)/1kVdc



References

Packaging	Specifications	Standard Packing Quantity
А	Ammo Pack	700

Mass (typ.)	
1 piece	0.59g

1 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of DE6E3KJ222MN3A from the official website of Murata

DE6E3KJ222MN3A



Specifications

L size or Outer diameter D	9.0mm max.	
T size	7.0mm max.	
Lead spacing F	7.5±1.0mm	
Lead diameter d	0.6±0.05mm	
Paint dripping e	Up to the end of crimp	
Capacitance	2200pF ±20%	
Rated voltage	300Vac(r.m.s.)	
Temperature characteristics	E(JIS)	
Capacitance change rate	+20/-55%	
Temperature range of	-25°C to 85°C	
temperature characteristics	20 0 10 00 0	
Operating Temperature	-40°C to 125°C	
Range		

2 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of DE6E3KJ222MN3A from the official website of Murata


DE6E3KJ222MN3A





Characteristic Data

The charts below may show another part number which shares its characteristics.









3 of 4

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering







Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of DE6E3KJ222MN3A from the official website of Murata

DE6E3KJ222MN3A



DE6E3KJ222MN3A C-Temp. capchange, DCOV, AC1V



DE6E3KJ222MN3A S21 DCOV,2OdegC

4 of 4

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

