

# GRM188R71E224KA88D

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of GRM188R71E224KA88# from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=GRM188R71E224KA88%23

"#"at the end indicates the package specification code.











< List of part numbers with package codes > GRM188R71E224KA88D GRM188R71E224KA88W GRM188R71E224KA88V

GRM188R71E224KA88J



## **Applications**

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	. ,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



### References

Packaging	Specifications	Standard Packing Quantity
D	φ180mm Reel Paper Tape	4000
W	φ180mm Reel W8P2 Paper Tape	8000
J	φ330mm Reel Paper Tape	10000
V	φ330mm Reel W8P2 Paper Tape	30000

Mass (typ.)	
1 piece	6.3mg



## Appearance & Shape





1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

 $2. This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$ 

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# GRM188R71E224KA88D

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of GRM188R71E224KA88# from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=GRM188R71E224KA88%23

"#"at the end indicates the package specification code.



## **Specifications**

1	.6±0.1mm	
0	0.8±0.1mm	
ess 0	).8±0.1mm	
cance 0	).22μF ±10%	
e between external	) 5mm min	
ls g	0.311111 111111.	
ıl terminal size e 0	0.2 to 0.5mm	
ng Temperature	55°C to 125°C	
	-55 € 15 125 €	
/oltage 2	25Vdc	
de in inch(mm)	0603 (1608M)	
tance change rate ±	15.0%	
rature characteristics	X7R(EIA)	
ed standard)		
rature range of	55°C to 125°C	
ature characteristics	-55 € 10 125 €	
tance  e between external  ls g  of the properties of the properti	0.22µF ±10% 0.5mm min. 0.2 to 0.5mm 55°C to 125°C 25Vdc 0603 (1608M)	

2 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

