



Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LDM182G5005CC001 from the official website of Murata

# LDM182G5005CC001











### **Applications**

Unsuitable	Please be sure to read and comply with		
Applications	these "Precautions for use."		
	Consumer equipment,Industrial		
	Equipment,Medical equipment [GHTF		
	A/B],Mobile Electronics		
	Please refer to Our Website and		
Cifi-	specifications, etc. for information about		
Specific Applications	the performance, functions, quality,		
	management, and safety required for		
	the above applications, and use		
	Products after confirming the		
	performance and reliability of the actual		
	Product.		
Recommended	Consumer equipment,Industrial		
	Equipment,Medical equipment [GHTF		
Applications	A/B],Mobile Electronics		



### Packaging Information

Packaging	Specifications	Standard Packing Quantity
-	180mm Paper Tape	4000



### **Features**


Chip type SMD baluns constructed with copper conductor and ceramic material.

Ideal for high-frequency applications.

- 1. Small, Low-profiled SMD.
- 2. Low loss.
- 3. Available in tape and reel packing for automatic mounting.



## Appearance & Shape



1 of 2

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





### Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of LDM182G5005CC001 from the official website of Murata

# LDM182G5005CC001



## **Specifications**

Center Frequency	2500.00MHz
Frequency Range	2300.00MHz to 2700.00MHz
Insertion Loss I)	0.90dB max. (at 25°C)
Insertion Loss II)	1.00dB max. (-40 to +85°C)
Unbalance Impedance (Nom.)	50Ω
Balance Impedance (Differential) (Nom.)	50Ω
Unbalance Port VSWR	2.00 max. (Balance Port:at 50ohm)
Operating Temperature Range	-40°C to 85°C
L x W (size)	1.60x0.80mm
Thickness(max.)	0.4mm

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

