Product Search Data Sheet



PV36W503C01B00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.


Please download the latest datasheet of PV36W503C01B00 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=PV36W503C01B00



Appearance & Shape







- 1. High resolution 25-turns potentiometer enables precision adjustment easily.
- 2. Sealed construction protects the interior from dust and liquid, which achieves stable performance.
- 3. Available for ultrasonic cleaning after soldering.
- 4. Clutch mechanism prevents excessive wiper rotation.



Packaging Information

Packaging	Specifications	Standard Packing Quantity
B00	Bulk(Bag)	100

1 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





PV36W503C01B00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of PV36W503C01B00 from the official website of Murata

http://www.murata.com/en/products/productdetail?partno=PV36W503C01B00



Power Rating 0.5W Shape Lead 300Vdc Maximum Working Voltage Adjustment Direction Тор Size 10mm No Auto Adjustment Number of Turns (Effective 25 Rotation Angle) Mechanical Rotation Angle **Total Resistance Value** 50kΩ Total Resistance Value ±10% Tolerance Temperature Coefficient of ±100ppm/°C Resistance **Resistance Taper** B (Linear) Less than 3% of total Contact Resistance Variation resistance value or 30hm, whichever is greater **Residual Resistance** 20hm max. 14.7mN · m max. Torque Measure Condition of 70°C RatedPower **Operating Temperature** -55°C to 125°C Range Mass 1g

2 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



Product Search Data Sheet




PV36W503C01B00

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

 $\label{eq:Please} Please \ \text{download the latest datasheet of PV36W503C01B00 from the official website of Murata}$

http://www.murata.com/en/products/productdetail?partno=PV36W503C01B00





Constructions

3 of 3

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

